International Journal of Advance Research in Science and Engineering Vol. No.4, Special Issue (01), September 2015

www.ijarse.com

IJARSE ISSN 2319 - 8354

STUDY OF POLLUTION STATUS IN RIVER GANGA AT PERMUT GHAT AND BHAIRAV GHAT IN 2013 IN KANPUR IN UTTAR PRADESH

R.C.Verma¹, A.B.Afridi², A.Kumar³

¹Deptt.of Chemistry, Janta P.G.College, Bakewar, Etawah (India)

²Deptt.of Chemistry, K.K. College, Etawah, (India)

³Deptt.of Zoology, K.K.P.G.College, Etawah, (India)

ABSTRACT

Water samples from river Ganga at Permut Ghat and Bhairav Ghat and in Kanpur in Uttar Pradesh were collected and phyco-chemical parameters were determined using standard analytical procedure in Jan.to Dec.2013.pH (7.4-9.1),chloride and phosphate contents of water samples were determined 10-18 mg/l and 0.08-0.16 ppm respectively. Total hardness 94.6-160.9 mg/l,fluoride level also 6.0-6.3 mg/l,DO of samples were 4.0-7.4 mg/l, BOD were 2.0-6.5 mg/l and COD were 12.0-39 mg/l. These results were said to their agreed with the limits set by World Health Orgnization (WHO) for drinking water.

Keyword: Pollution Status, WHO, Drinking Water.

I. INTRODUCTION

Water the most essential requisites that nature has provided to sustain life on earth. About 80% earth surface is covered by water. The deteriorate quality of water create various problems for mankind. The growth in population, about 90% of which occur in uebon area, increases the demand for water for domestic and industrial uses. Water pollution from domestic and human waste is the main cause for human being water born desease. The industrial water pollution is due to inadequate measure adopted in the industry for the abatement of pollution. It is need of time to protect environment for present and future generations. The purpose of study into prepares qualitative assessment of abiotic and biotic conditions prevailing in river Ganga.

II. MATERIAL AND METHOD

The Kanpur on National Highway no.1 and 2 falls on Broad Gauge NR Railway line between Delhi and Kolkata.

Water samples were collected in clean polythene bags and subjected to chemical analysis for measurement of different parameters such as temperature, pH,DO,BOD,COD, fluoride, chloride, phosphate ,hardness and total dissolved by standered analytical methods in Jan. to Dec.2013.

International Journal of Advance Research in Science and Engineering

Vol. No.4, Special Issue (01), September 2015

www.ijarse.com

III. RESULT AND DISCUSSION



The values of different parameter with respect to sampling stations (Permut Ghat and Bhairav Ghat) are given in Table-1 and Table-2. The transparency values of samles were 21.0-54.5 cm. Maximum value is 54.5 in Jan. 2013 at Bhairav Ghat while minimum value is 21.0 in Aug. 2013 at Permut Ghat . The temperature of water was 16.2-36.2°C. Maximum value is 36.2 in Jun. 2013 at Bhairav Ghat while minimum is 16.2 in Jan. 2013 at Bhairav Ghat. The WHO(1992) did not recommend any definite temperature for drinking water. The pH value were 7.4-9.1. Maximum value is 9.1 in Dec. 2013 at Bhairav Ghat while minimum value is 7.4 in May, 2013 at Bhairav Ghat.

Total dissolved were 134-140 mg/l. Maximum value is 140 mg/l in Jul.2013 at Bhairav Ghat while minimum value is 134 mg/l in Jan 2013 at Permut Ghat, which are under limits. The total hardness of water were 94.6-160.9 mg/l. The maximum value is 160.9 in Jun. 2013 at Bhairav Ghat while minimum value is 94.6 in Sept.2013 at Bhairav ghat. The levels of hardness are below the level(300 mg/l) as laid down by Indian standard and thus water is soft. Fluoride level were 6.0-6.3 mg/l. The maximum value is 6.3 in Jun. & Jul.2013 at Bhairav Ghat Ghat and in Jul,2013 at Permut Ghat while minimum value is 6.0 in Apr.2013 at Bhairav Ghat and in May at Permut Ghat ,which are low. The chloride contents were 10-18 mg/l. The maximum value is 18 mg/l in Jun. & Dec.2013 at Jajamau Bhairav Ghat while minimum value is 10 mg/l in Aug. & Sept.2013 at Permut Ghat, which is below the prescribed limit (250 mg/l). The COD value were 12.0-39.0 mg/l. The maximum value is 39.0 mg/l in Apr.2013 at Permut Ghat while minimum value is 12 mg/l in Jul. & Aug.2013 at Permut Ghat.

The DO values were 4.0-7.4 mg/l. The maximum value is 7.4 in Dec.2013 at Bhairav Ghat while minimum value is 4.0 in Jun.2013 at Permut Ghat, which are permissible. The BOD values were 2.0-6.5 mg/l.The maximum value is 6.5 in Jan. & Jun.2013 at Bhairav Ghat while minimum value is 2.0 in Jul. & Aug.2013 at Permut Ghat.

Table-1Physico-Chemical Characterstics in River Ganga at Permut Ghat, Kanpur

Month	Temper	Transpare	pН	DO(mg/	BOD(m	COD(m	Chlorid	Phosph	Total	TDS(Fluoride
	ature	ncy(cm)		1)	g/1)	g/1)	e(ppm)	ate(mg	hardness(mg/l)	(mg/l)
	(⁰ C)							/1)	mg/l)		
Jan.	16.2	54.5	8.8	7.0	6.5	37.0	18.0	0.14	110.2	135	6.2
Feb.	18.8	53.5	8.7	6.5	6.0	36.0	17.0	0.14	105.7	135	6.2
Mar.	23.4	40.0	8.5	4.2	6.0	36.0	17.0	0.14	136.6	136	6.1
Apr.	31.8	38.5	8.7	5.2	5.0	30.0	16.0	0.15	148.7	136	6.0
May	35.7	28.0	7.9	5.8	5.5	38.0	16.0	0.12	156.3	138	6.2
Jun.	36.2	22.0	8.0	6.1	6.5	29.0	15.0	0.16	160.9	139	6.3
Jul.	28.6	26.0	8.8	6.2	4.0	29.0	15.0	0.15	95.7	140	6.3
Aug.	23.4	22.0	8.9	6.5	4.0	28.0	15.0	0.16	96.3	138	6.2
Sept.	24.6	25.0	8.9	6.0	4.5	25.0	16.0	0.12	94.6	137	6.2
Oct.	18.3	27.5	8.4	6.8	3.5	36.0	17.0	0.09	95.4	136	6.1
Nov.	18.0	36.5	9.0	7.2	3.5	28.0	16.0	0.08	97.6	137	6.2
Dec.	18.4	50.5	9.1	7.4	3.0	36.0	18.0	0.09	98.6	137	6.1

International Journal of Advance Research in Science and Engineering

Vol. No.4, Special Issue (01), September 2015

www.ijarse.com



Table-2 Physico-Chemical Characterstics in River Ganga at Bhaieav Ghat, Kanpur

Mont	Temper	Transpar	pН	DO(mg/	BOD	COD(m	Chlorid	Phosphate	Total	TDS(m	Fluo
h	ature(0	ency(cm		1)	(mg/l)	g/l)	e(ppm)	(mg/l)	hardness(mg	g/l)	ride(
	C))							/I)		mg/l
)
Jan.	16.3	52.0	8.3	7.2	3.5	35	15	0.12	114.2	134	6.1
Feb.	18.2	52.5	8.2	6.8	3.0	34	14	0.11	106.2	135	6.2
Mar.	23.1	39.0	8.1	6.5	4.0	34	16	0.13	135.5	136	6.1
Apr.	31.6	37.5	7.8	4.0	4.5	39	15	0.14	155.2	136	6.1
May	35.8	31.0	7.4	4.8	4.0	38	14	0.14	158.2	135	6.0
Jun.	36.0	21.5	7.9	4.2	5.0	13	15	0.16	160.3	136	6.2
Jul.	28.4	37.0	7.6	5.4	2.0	12	11	0.15	97.4	137	6.3
Aug.	23.9	21.0	7.9	5.9	2.0	12	10	0.15	97.5	139	6.2
Sept.	24.8	26.0	7.8	6.2	3.5	28	10	0.14	99.6	138	6.1
Oct.	18.1	27.0	8.2	6.8	3.5	29	11	0.13	94.7	135	6.1
Nov.	18.8	37.5	8.4	6.7	2.5	28	14	0.12	95.8	136	6.2
Dec.	18.2	49.5	8.1	6.9	2.5	36	15	0.12	95.9	137	6.1

IV. CONCLUSION

It is need of time to protect environment for present and future generation. The purpose of study is to prepare qualitative assessment of biotic and abiotic conditions prevailing in river Ganga.

REFERENCES

- [1]. American Public Health Association, American Water Works Association, and Water Pollution control Feseration, Standard methods for the examination of water and wastewater, 18th Ed. Washington D.C. USA, American Health Association variously paginated. 1992.
- [2]. ICMR Manual of standard of quality for drinking water supplies. ICMR, New Delhi. 1975.
- [3]. WHO (World Health Organization). Environmental health criteria, vol.134-Cadmium international programmed on Chemical Safety (IPCS) Monograph. Geneva, Switzerland.
- [4]. SI, Indian Standard Specification for drinking for water:ISI, 1983, 10500.
- [5]. Indian standard methods of sampling and test (Physical & chemical) for water used to industry, Indian Standard Institution, New Delhi IS, 3025,1964.
- [6]. Rai,M. and Srivastava,R.M.,Metallic status in and around Chopan River Radhogarh,Cur.W.Envir.2006,1 (1) 91-93
- [7]. Rajesh C.V., Jitendra G. and Raghav S., Study of Physico-chemical characteristics and heavy metals in river Sengar at Jaswant Nagar District Etawah in Uttar Pradesh, Int. J. of pharm.res. and bio-sc. 2014, 3 (3) 108-111.
- [8]. Vishwakant, Verma, R.C. and Saxena, R.S., Study of some limnological properties of Harchandpur pond, District Etah, Cur. W. Envir., 2006, 2(1);35-38 (2007)

International Journal of Advance Research in Science and Engineering

Vol. No.4, Special Issue (01), September 2015

www.ijarse.com

- [9]. Verma,R.C.,Mishra,P. and Sambhavi: Study of Phyco-chemical chaeacterstics river Ganga at Bithoor Ghat in Winter in District in Uttar Pradesh;GE-Int.J.Engg.Res.,2014,vol.-2,issue-5,125-128.
- [10]. Verma,R.C. and Bansal,A.:Study of Physico-chemical characteristics in river Ganga at Bithoor Ghat in District Kanpur in Uttar Pradesh,Am.Int.J.of Res.in Formal,Appl. And Nat.Sc.,2014,7(1),June-Aug.79-80.
- [11]. Verma,R.C.,Raghav,S.and Kumari,M.: Study of pollution ststus in River Ganga at Sarsaiya Ghat im District Kanpur in Uttar Pradesh, Int.J.of Adv.Tech.in Engg. And Sc.,2015,vol-3,spl.issue-02,Feb.,605-607.
- [12]. Elick,H.S. and Solomoon,R.J.: The Physico-chemical parameters of Souka River in the FCT Abuja,Int.J.of Bioassays,2015,4(07),4036-4049.
- [13]. Verma,R.C.,Raghav,S. and Kumari,O.: Study of physico-chemical characteristics in River Ganga at Sarsaiya Ghat and Gola Ghat in 2013 in District Kanpur in Uttar Pradesh,2015,vol.-4,spl.issue (01) Aug.2015,144-147.