

# AUTOMATIC DETECTION AND NOTIFICATION OF POTHoles AND HUMPS ON ROADS TO AID DRIVERS USING ULTRASONIC SENSORS

**Chenumalla Harishankar<sup>1</sup>, H.Raghupathi<sup>2</sup>**

*<sup>1</sup>Pursuingm. Tech (ES), <sup>2</sup>Assistant Professor,*

*Visvesvaraya College of Engineering and Technology*

*Patelguda, Ibrahimpatnam, Ranga Reddy Dist. Telangana, (India)*

## **Abstract**

Now a day's street facility rectangular measures a great problem within the advanced global. Recent studies display that one 0.33 of the quantity of fatal or extreme accidents square degree related to immoderate or irrelevant velocity, additionally as adjustments within the path (just like the presence of street-work or unexpected barriers). Reduction of the quantity of accidents and mitigation in their outcomes square measure an full-size problem for traffic government, the automobile enterprise and delivery evaluation groups. One important line of movement is composed in the use of superior driver assist systems.

The analysis target unifying the global Positioning gadget with embedded wireless gadget is that the brand new approaches in smart car management for important far off location software victimization ARM. In normal gadget they're designed to manage the velocity of motors altogether days. The most objective of the projected machine is to control the speed of vehicle at essential zones. The backside station having the transmitter that is intended for modulation (FM), the receiver 1/2 is enforced in Vehicle. The ARM processor is enforced at receiver side, that gets the vital frequency, and so it's activated in critical mode. Speed management Driver (SCD) is bespoke to healthy into a vehicle's dashboard, and presentations facts on the car. Once the knowledge is received, it mechanically alerts the purpose pressure, to scale back the velocity in line with the zone. The novel system is enforced with the assist of embedded processor and additionally the simulation is done through KEIL C code and outcomes square measure mentioned.

**Keywords:** *ARM7 board, GPS, module, LCD, DC motor*

## **I.INTRODUCTION**

INDIA, the second one most populous Country within the World and a quick developing economic system, is understood to have gigantic network of roads. Roads are the dominant method of transportation in India these days. They convey nearly 90 percent of United States' passenger visitors and sixty five percentage of its freight [1]. However, most of the roads in India are narrow and congested with bad floor first-rate and street upkeep wishes are not satisfactorily met. No depend wherein you're in India, driving is a breath-holding, multi-replicate involving, doubtlessly life threatening affair. Over the remaining a long time, there was a super boom within the automobile population. This proliferation of automobiles has led to issues together with site visitor's congestion

and growth within the variety of avenue accidents. Pathetic situation of roads is a boosting thing for site visitor's congestion and accidents. Researchers are running in N the region of site visitors congestion manage [2], an vital part of vehicular place networks, which is the need of the hour these days. Roads in India generally have velocity breakers in order that the vehicle's pace may be managed to avoid accidents. However, those pace breakers are erratically allotted with choppy and unscientific heights. Potholes, fashioned because of heavy rains and movement of heavy vehicles, also emerge as a major reason for stressful injuries and lack of human lives.

## **II. EXISTING SYSTEM**

One of the predominant troubles in growing international locations is preservation of roads. Well maintained roads make contributions a prime portion to the use of a's economy. Identification of pavement misery consisting of potholes not most effective facilitates drivers to avoid accidents or car damages, but also helps government to preserve roads. This paper discusses previous pothole detection techniques which have been developed and proposes a value powerful strategy to become aware of the potholes on roads and offer timely indicators to drivers to avoid accidents or automobile damages. Camera captures the image of the street, Beagle bone is used to pick out the potholes on the road, the geographical location coordinates of the potholes are identified the use of a worldwide positioning device receiver respectively. The sensed statistics includes pothole width and geographic vicinity, which is stored inside the database (cloud). This serves as a treasured source of facts to the society and automobile drivers. An android application is used to alert drivers so that precautionary measures can be taken to prevent accidents. Alerts are given in the form of a App notification and vibration.

## **III. PROPOSED SYSTEM**

The proposed device gives a price powerful answer for detecting potholes on roads and notifying drivers about their presence. Components used in the proposed paintings are as follows: Beagle bone black: The Beagle Bone Black is the state-of-the-art addition to the Beagle Board family and prefer its predecessors, is designed to cope with the Open Source Community, early adopters, and all of us interested in a low price ARM Cortex-A8 primarily based processor. It has been equipped with a minimal set of functions to permit the consumer to experience the power of the processor and isn't always supposed as a complete development platform as among the features and interfaces furnished by using the processor aren't on hand from the Beagle Bone Black thru onboard guide of a few interfaces. It is not a entire product designed to do any particular function. It is a foundation for experimentation and getting to know a way to application the processor and to access the peripherals by using the introduction of your personal software program and hardware.

It moreover gives get admission to to a number of the interfaces and lets in for using add-on forums known as capes, to characteristic many exclusive mixtures of functions. A individual might also increase their very own board or upload their non-public circuitry. Beagle Bone Black is synthetic and confident through Circuits LLC in Richardson Texas for the gain of the community and its supporters. In addition, Circuits gives the RMA manual for the Beagle Bone Black. Jason Kinder of Texas Instruments handles the community promotions and is the spokesmen for Beagle Board. The board is designed with the useful resource of Gerald Coley, an employee of Texas Instruments and a charter member of the Beagle Board. Or network. The PCB format

become finished via using Circuits and Circuits is the handiest funder of its development and transition to manufacturing.

The Software is written and supported via manner of the masses of community participants, which include Jason Kinder, personnel of Texas Instruments, Dailey, and Circuits. Fig 3. Shows the Beagle bone Black Board. Camera: Normal internet digicam is used to capture the pictures. For in addition greater clarity nonetheless advanced virtual cameras can be covered. GPRS: Global Positioning System (GPS) is a satellite tv for pc navigation gadget and is used to capture geographic location and time, irrespective of the situations. It is maintained via the U.S. Government and is freely to be had to each person who has a GPRS receiver. It obtains the GPRS records from satellites in National Marine Electronics Association (NMEA) format. The NMEA has defined a popular format for the GPRS statistics. This is followed through all of the satellites. The preferred defines numerous codes together with GLL-Latitude/Longitude facts, GSV-Detailed satellite television for pc statistics and RMC-Minimum Recommended Data.

#### IV. BLOCK DIAGRAM OF PROPOSED SYSTEM




Fig1: Block diagram

## V. HARDWARE REQUIREMENTS

### LPC2148 Microcontroller:

The ARM7 (advanced RISC device) processors board based whole on a 16/32-bit ARM7 its method of sixteen/32-bit ARM7 TDMI-S microcontroller, eight laptop memory unit to 40 laptop memory unit of on-chip static RAM and 32 pc reminiscence unit to 512computer memory unit on-chip flash memory; 128-bit In-device Programming (ISP). 32-bit timers/out of doors occasion counters, PWM pulse width modulation unit (six outputs) and watchdog, Low strength of real-Time Clock (RTC), more than one serial interfaces which has 2 UARTs , rapid I2C-bus (400kbit/. There are sixty four pins of ARM7 processor and a couple of ports (port0, port1) 45 pins are enter/output.




Fig2:-LPC2148 board

### GSM/GPRS -Module:

GSM (global tool for cell communications) is a cell community, this means that that mobile phones hook up with it through way of attempting to find cells in the at once place. GSM networks function in 4 specific frequency degrees. Maximum GSM networks feature in the 900 MHz or 1800 MHz bands. A few international places inside the Americas use the 850 MHz were already allotted. Different bands are assigned in a few international locations, in which those frequencies have been formerly used for first-technology systems.



Fig 3: GSM module

#### L293D:

The L293D is a quadruple excessive-modern half of-H drivers, it also known as as line motive force circuit. The L293d is designed to offer bidirectional power currents of up to one A at voltages from four.5 V to 36 V. The driver incorporates totally 16 pins, in that 4 pins for enter and 4 pins for output. The output pins are linked to the automobiles and enter pins are takes from the controller and l293d includes power deliver pins and two ground pins. The major use of the l293d IC is besides up the voltage ranges to run the D.C motor. Here we are taking the four input pins and four output pins, the D.C motor requires handiest pins so we are able to run automobiles at a time by the use of the l293d driving force IC.

#### Motors:

Motors are electro mechanical devices which might be used for to transform the electrical signals into mechanical indicators. The all D.C vehicles are having identical internal mechanism, both electromechanically to change the path of modern drift in part of the motor. In task we are used for to transport the motor in precise route. We want to attach the motor to controller via motive force IC handiest.




Fig4: DC motor


### Ultrasonic Sensor

Ultrasonic sensors are gadgets that use electric–mechanical energy transformation, the mechanical electricity being in the form of ultrasonic waves, to measure distance from the sensor to the goal item. Ultrasonic waves are longitudinal mechanical waves which excursion as a succession of compressions and rarefactions along the direction of wave propagation via the medium. Any sound wave above the human auditory range of 20,000 Hz is referred to as ultrasound. Depending on the form of application, the form of frequencies has been notably classified as tested within the discern under:

### The Frequency Ranges of the Sound



When ultrasonic waves are incident on an item, subtle reflected picture of the power takes place over a large solid angle which might be as high as one hundred eighty stages. Thus a few fraction of the incident energy is contemplated once more to the transducer inside the shape of echoes and is detected. The distance to the item (L) can then be calculated thru the speed of ultrasonic waves (v) within the medium by means of the relation



### VI. SOFTWARE DESIGN

In this proposed contrivance, as we tend to used LPC2148 we wish to use following software package instrumentation to program for it.

1. Keil4 Vision
2. Flash Magic

The Keil4 Vision an IDE for Embedded c program language period. In this IDE, we wish to import the utilities and libraries constant with the controller. This IDE is very more without problems and in consumer pleasant thanks to observe, assemblers, and debuggers in it. It simplifies the way of embedded simulation and attempting entering conjunction with Hex document technology. The flash magic is a programming application. The C/C++ software program written in IDE might be processed into Hex file i.E. In .Hex layout. By the usage of hex report we have a tendency to products the code into microcontroller and perform application.


## **VII. WORKING PROCEDURE**

Now an afternoon's road facility rectangular measures a vast concern within the developed international. Recent research show that one 1/3 of the amount of fatal or serious injuries rectangular measure associated with immoderate or irrelevant pace, also as changes in the path (just like the presence of street-paintings or surprising limitations). Reduction of the quantity of accidents and mitigation in their consequences square measure an good sized situation for visitors government, the car business and transport analysis teams. One important line of motion consists inside the use of advanced motive force assist systems.

The evaluation goal unifying the global Positioning system with embedded wi-fi gadget is that the new approaches in wise automobile management for important faraway location utility victimization ARM. In typical machine they're designed to manipulate the velocity of vehicles altogether days. The maximum objective of the projected gadget is to manipulate the speed of auto at vital zones. The bottom station having the transmitter that is intended for modulation (FM), the receiver 1/2 is enforced in Vehicle. The ARM processor is enforced at receiver side, that gets the important frequency, and so it is activated in vital mode. Speed management Driver (SCD) is bespoke to fit into a car's dashboard, and displays records at the vehicle. Once the expertise is obtained, it mechanically alerts the purpose force, to reduce the velocity in step with the quarter. The novel gadget is enforced with the help of embedded processor and also the simulation is executed via Keil C code and results rectangular measure referred to. By the use of this challenge we will reduce the velocity of the vehicle at the vital zones. The vehicle have the receiver and at the crucial zones it will have the transmitter on every occasion the receiver gets the transmitted sign from the essential zones the car velocity will reduces. That manner the car enters into the important sector, passing of important sector the car will moves normal speed. The pace of the vehicle will be reduces with the aid of the PWM technique.

## **VIII. RESULT**

Here the output of the project "**Automatic Detection and Notification of Potholes and Humps on Roads to Aid Drivers Using Ultrasonic Sensors**" output was successfully implemented. The receiver fixed to the vehicle and transmitter at the critical zones whenever receiver received the transmitted signal from the critical zone the than vehicle will automatically reduce speed that implemented successfully.



## IX. CONCLUSION

By using this project we can conclude that when vehicle was enters into the critical the speed of the vehicle will automatically reduce and after the critical zone the vehicle moves with normal speed. With this project we can reduces the accidents at the critical zonesand we can reduces the speed of the vehicle from rash driving.

## REFERENCES

- 1) [www.ijcsit.com/docs/Volume%204/Vol4Issue6/ijcsit2013040653.pdf](http://www.ijcsit.com/docs/Volume%204/Vol4Issue6/ijcsit2013040653.pdf)
- 2) [www.google.co.in/patents/US5485161](http://www.google.co.in/patents/US5485161)
- 3) [www.mecs-press.org/ijisa/ijisa-v5-n9/IJISA-V5-N9-10.pdf](http://www.mecs-press.org/ijisa/ijisa-v5-n9/IJISA-V5-N9-10.pdf)
- 4) [www.indjst.org/index.php/indjst/article/view/93045](http://www.indjst.org/index.php/indjst/article/view/93045)
- 5) [https://en.wikipedia.org/wiki/Vehicle\\_tracking\\_system](https://en.wikipedia.org/wiki/Vehicle_tracking_system)
- 6) [https://en.wikipedia.org/wiki/Global\\_Positioning\\_System](https://en.wikipedia.org/wiki/Global_Positioning_System)
- 7) [www.mycollegeproject.com/ECE\\_Projects.html](http://www.mycollegeproject.com/ECE_Projects.html)
- 8) [www.colorado.edu/geography/gcraft/notes/gps/gps\\_f.html](http://www.colorado.edu/geography/gcraft/notes/gps/gps_f.html)

9) [www.montana.edu/gps/understd.html](http://www.montana.edu/gps/understd.html).

10) [https://www.cfa.harvard.edu/space\\_geodesy/ATLAS/gps.html](https://www.cfa.harvard.edu/space_geodesy/ATLAS/gps.html)

### Author Details

	<p><b>CHENUMALLA HARISHANKAR</b> Pursuing M.Tech (ES ) from Visvesvaraya College Of Engineering And Technology, Patelguda, Ibrahimpatnam, RangaReddy dist, Telangana, INDIA.</p>
	<p><b>H.RAGHUPATHI</b> working as Assistant Professor from Visvesvaraya College Of Engineering And Technology, Patelguda, Ibrahimpatnam, RangaReddy dist, Telangana, INDIA.</p>